



Retail Price Schedule

Effective September 1, 2000
Supersedes all previous price schedules

Item Number	Item Name	Description	Retail Price
1229 PKG.	Amplifier TST 229 Package Special	Two (2) TST229 One (1) Amp One, Two (2) XCF 50 Crossovers, Two Year Warranty	\$699.99
TST 229	Tactile Sound™ Transducer	Magnet: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt Application: Single seating In home theater and car Installation	\$199.95
TST 329	Tactile Sound™ Transducer	Magnet: 20 oz. Neodymium, Tactile Force: >2.8 lbs/watt Polyswitch Protected Application: Risers and seating In home theater Installations	\$499.95
TST 3710	Tactile Sound™ Transducer	Magnet: 25 oz. Neodymium, Tactile Force: >3.5 lbs/watt Polyswitch Protected Application: Risers and seating In home theater Installation	\$599.95
PLATINUM I	Tactile Sound™ Transducer	Magnet: 25 oz. Neodymium, Tactile Force: >6.9 lbs/watt Application: Risers and seating In home theater Installation producing maximum low end response	\$699.95
TST 229WP	Weather Proof Tactile Sound™ Transducer	Magnet: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt Polyswitch Protected Application: Decks Benches and outdoor use, high humidity environments	\$239.95
TST 329WP	Weather Proof Tactile Sound™ Transducer	Magnet: 20 oz. Neodymium, Tactile Force: >2.8 lbs/watt Polyswitch Protected Application: Decks Benches and outdoor use, high humidity environments	\$529.95
TST 3710WP	Weather Proof Tactile Sound™ Transducer	Magnet: 25 oz. Neodymium, Tactile Force: >3.5 lbs/watt Polyswitch Protected, Weather Proof Application: Decks and outdoor use high humidity environments	\$629.95
TST 229 WT	Water Tight Tactile Sound™ Transducer	Magnet: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt Water Tight submersible 60 p.s.i.g. Application: Retro-- fit spas Marine applications boat hulls, bilge's	\$259.95
TST 329 WT	Water Tight Tactile Sound™ Transducer	Magnet: 20 oz. Neodymium, Tactile Force: >2.8 lbs/watt, Water Tight submersible 60 p.s.i.g. Application: Retro-- fit spas Marine applications boat hulls, bilge's	\$549.95
TST 3710 WT	Water Tight Tactile Sound™ Transducer	Magnet: 25 oz. Neodymium, Tactile Force: >3.5 lbs/watt, Water Tight submersible 60 p.s.i.g. Application: retro-- fit spas Marine applications boat hulls, bilge's	\$649.95
Aqua 229	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt Sound Lens for high fidelity sound, Application: Small Pools, Spas	\$359.95
Aqua 329	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 20 oz. Neodymium, Tactile Force: >2.8 lbs/watt Sound Lens for High fidelity sound, Application: Pools, Spas, Underwater communication	\$599.95
Aqua 3710	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 25 oz. Neodymium, Tactile Force: >3.5 lbs/watt Sound Lens for high fidelity sound, Application: Pools, Spas, Underwater communication	\$699.95
TST 229 WTL	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt Application: Flush mount in American Products Amerlite light niche'underwater swimming pool light fixture	\$339.95
TST 329 WTL	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 20 oz. Neodymium, Tactile Force: >2.8 lbs/watt Polyswitch Protected Application: Flush mount in American Products Amerlite light niche'underwater swimming pool light fixture	\$575.95
TST 3710 WTL	Aquasonic [®] Tactile Sound™ Underwater Speaker	Magnet: 25 oz. Neodymium, Tactile Force: >3.5 lbs/watt Highest Fidelity & Output Application: Flush mount in American Products Amerlite light niche'underwater swimming pool light fixture	\$675.95
Amp 1	Amplifier	Amplifier , 2 Channel, 135 Watts per channel at 4 , Front panel gain control, Mono Bridgeable, Stable into 2 , Line out jacks, unswitched 120v outlet .04THD. 110 db S/N Dimensions 16 1/2W X 2 3/8H X 11 5/8D	\$299.95
Amp 3	Amplifier	Amplifier , 2 Channel, 240 Watts per channel at 4 , Front panel gain control, Mono Bridgeable, Stable into 2 , Line out jacks, A & B Speaker Switching, .04THD. Dimensions 16 1/2W X 2 3/8H X 11 5/8D	\$549.95
Amp 5.2	Amplifier	Amplifier ,1 Channel, 240 Watts at 4 , Front panel gain control, Stable into 2 , RCA and XLR inputs, small profile. Dimensions 5 1/2W X 4 1/2H X 11 1/2D	\$249.95
EQ 2	Graphic Equalizer	Graphic Equalizer Ten Band Stereo, Spectrum analyzer display, Channel Level controls, Two stereo line inputs, Dual Tape monitor loops, unswitched 120v outlet .01THD. Dimensions 16 1/2W X 3 1/2H X 11 1/2D	\$159.95
LLC	Line Level Converter	Converts Line level (speaker level) to RCA (low level) Made in USA	\$34.95
Y3	Y Cable	Gold Plated "Y" Splitter, 2 female X 1 Male RCA connector	\$7.95
XCF500	Crossover	500Hz Low Pass Gold Plated inline crossover 12db per octave Application: reduce localization and high frequencies in home theater applications.	\$34.95
XCF200	Crossover	200Hz Low Pass Gold Plated inline crossover 12db per octave Application: Reduces localization and high frequencies in home theater applications.	\$34.95
XSF20	Subsonic Filter	Sub sonic Gold Plated inline crossover 12db per octave Application: Reduces ultra low frequencies in signal that is not needed in some applications.	\$34.95
DTM	Drum Throne Mounting Bracket	Drum Mount for transducers, makes mounting to a drum throne simple use with one of the Tactile Sound™ Transducer s listed above. Includes connector for XLR and 1/4 inch speaker cable	\$99.95
DTST229F	Tactile Sound™ Transducer and Drum Mounting Bracket	TST 229F Tactile Sound™ Transducer with DTM mounting kit included Magnet Structure: 20 oz. Ceramic, Tactile Force: >1.6 lbs/watt	\$269.95
DTST329 Pro	Tactile Sound™ Transducer and Drum Mounting Bracket	TST 329F Tactile Sound™ Transducer with DTM mounting kit included Highest force per watt and power handling Magnet Structure: 20 oz. Neodymium Tactile Force: >2.8 lbs/watt	\$549.95
DTST3710 Super Pro	Tactile Sound™ Transducer and Drum Mounting Bracket	TST 3710 Tactile Sound™ Transducer with DTM mounting kit included Highest force per watt and power handling Magnet Structure: 25 oz. Neodymium Tactile Force: >3.5 lbs/watt	\$649.95
DTSTPLATINUM I	Tactile Sound™ Transducer and Drum Mounting Bracket	Platinum I Tactile Sound™ Transducer with DTM mounting kit included Magnet: 25 oz. Neodymium, Tactile Force: >6.9 lbs/watt Highest Bass & Low Frequency Output	\$749.95

CLARK SYNTHESIS, Inc.

8122 Southpark Lane • Suite 110 • Littleton Colorado • 80120

Voice: 303-797-7500 • Toll Free: 800-898-1945 • Fax: 303-797-7501 • E-mail: info@clarksynthesis.com • Web: www.clarksynthesis.com

Terms and Conditions of Sale:

Freight Policy: FOB Factory, Littleton, CO. USA Dealer Orders shipped prepaid with appropriate freight charges added to each invoice

Payment Terms: Net 30 days from invoice date (on approved credit), C.O.D. or payment in advance via check or Visa/Mastercard

Warranty Return: All returns must be marked with a material return authorization (RMA) number issued by Clark Synthesis and shipped freight prepaid in original condition and packaging.